

YOU DESERVE



Date:

Project:

Prepared for:

Type:

Comments:

LED SLIM PANELS

PRODUCT OVERVIEW

Introducing our innovative Slim Panel, a versatile lighting solution that combines sleek design with exceptional performances. This round panel is crafted in a white, brushed nickel or black finish, adding a touch of elegance to any space. With its 5CCT selectable feature, you have the flexibility to choose between five different correlated color temperatures (CCT) to create the perfect ambiance.



ARANI LED Slim Panels Specifications

Electrical Characteristics	<ul style="list-style-type: none"> • Input current: 205mA for SL4, 340mA for SL6 • Input Voltage: 110-130Vac 60Hz • Rated Power: 9W for the 4" and 15W for the 6" • Power factor: >0.94
IP Rating	<ul style="list-style-type: none"> • Suitable for wet locations
IC Rating	<ul style="list-style-type: none"> • Type IC
LED Chip & LED Quantity	<ul style="list-style-type: none"> • SMD2835 • Edge-lite • 48pc for the 4" • 72pc for the 6"
Colour Temperature	<ul style="list-style-type: none"> • Selectable between 2700K/3000K/3500K/4000K and 5000K
Beam Angle	<ul style="list-style-type: none"> • 110°
Colour Rendering Index	<ul style="list-style-type: none"> • 80+
Lumen output	<ul style="list-style-type: none"> • 660lm at 3000K for SL4, 1100lm for SL6
Operating Temperatures	<ul style="list-style-type: none"> • -20°C to 40°C
Dimmable	<ul style="list-style-type: none"> • Triac Base
Sizes Available	<ul style="list-style-type: none"> • 4" • 6"
Colours Available	<ul style="list-style-type: none"> • White • Brushed Nickel • Black
Codes & Standards	<ul style="list-style-type: none"> • Energy star • ETL • FCC (For SL4 only)
Lifetime	<ul style="list-style-type: none"> • 50 000 hours




Date:	Project:
Prepared for:	Type:
Comments:	

COLOURS AND SIZES

4" Slim Panels



SL4-VAR-R-BK-V3



SL4-VAR-R-BN-V3



SL4-VAR-R-WH-V3

6" Slim Panels



SL6-VAR-R-BK-V3










SL6-VAR-R-BN-V3



SL6-VAR-R-WH-V3

ORDERING INFORMATION

Series	Rated Power	Equivalent to	LED Qty	Colour Temp	Lumen Output	Cut out	Dimensions	Trim Colour	Ordering Code
4" Slim Panel	9W	60W	48	CCT Selectable 2700K 3000K 3500K 4000K 5000K	2700K: 606 3000K: 660 3500K: 690 4000K: 707 5000K: 678	3.7"	Ø 4.75" x 1" (Ø 12.07cm x 2.54cm)	White	SL4-VAR-R-WH-V3 
								Brushed Nickel	SL4-VAR-R-BN-V3 
								Black	SL4-VAR-R-BK-V3 
6" Slim Panel	15W	100W	72	CCT Selectable 2700K 3000K 3500K 4000K 5000K	2700K: 1080 3000K: 1100 3500K: 1185 4000K: 1218 5000K: 1139	5.7"	Ø 6.7" x 1" (Ø 17.02cm x 2.54cm)	White	SL6-VAR-R-WH-V3 
								Brushed Nickel	SL6-VAR-R-BN-V3 
								Black	SL6-VAR-R-BK-V3 

 *This icon indicates a STOCK item: Look for this Same Day Shipping icon below in 'Ordering Information' for products that ship on the same day (orders placed before 3pm) from Montreal, Quebec / Calgary, Alberta



Date:	Project:
Prepared for:	Type:
Comments:	

APPROVED DIMMERS


List of approved dimmers for our Slim Panels




The dimmers below have been tested and found to function properly with the specified product. Absence of a dimmer model on this list does not indicate incompatibility with the product, it means that they have not been tested:

Dimmer	Flicker
Arani DM1-150W-SL-3-WH-V2	NO
Leviton 6618	NO
Leviton RPI06	NO
Leviton 6631	NO
Leviton 6681-W	NO
Leviton IPL-06	NO
Leviton 6633	NO
Leviton 6621	NO
Leviton 6674	NO
Lutron SCL-153PH-WH-C	NO
Lutron CTCL-153PDH-WH-C	NO
Lutron S-603PG	NO

Dimmer	Flicker
Lutron S-600	NO
Lutron SLV-600P	NO
Lutron DVCL-153P-WH	NO
Lutron PD-6WCL	NO
Cooper RI306P-VW-K2	NO
Cooper SI10P	NO
Cooper SI061-W-K	NO
Eaton SUL06P	NO
TP-LINK Kasa Smart-HS220	NO

OPTIONAL MOUNTING PLATES



Series	Compatible with	Case Pack Qty	Ordering Code
4" Mounting Plate	4" LED Slim Panel V3	200	SL4-MP-R-V2 
4" Mounting Plate (long)	4" LED Slim Panel V3	50	SL4-MP-R-L-V2 
6" Mounting Plate	6" LED Slim Panel V3	50	SL6-MP-R-V2 




Date:	Project:
Prepared for:	Type:
Comments:	

OPTIONAL EXTENSION CABLE

If you need to extend the distance between the driver box and the light fixture, you can use our optional 4ft extension cables to increase the distance to a maximum of 24 feet. They are sold separately from the fixtures. This option is available for Gimbals and High Lumen Gimbals too.




4ft Extension Cable
EX-SLFL-4FT


Series	Compatible with	Length	Ordering Code
Extension Cable	LED SLim Panel V3	4ft	EX-SLFL-4FT 

OPTIONAL GOOF RINGS


If the hole where the fixture is to be installed is larger than the trim of the fixture, you can use our optional goof rings to expand the coverage diameter. They are sold separately from the fixtures.






5 1/2" Goof Ring
SL4-GR-WH-512-V1



7 5/8" Goof Ring
SL6-GR-WH-758-V1



8 5/8" Goof Ring
SL6-GR-WH-858-V1

Series	Compatible with	Colour	Ordering Code
5 1/2" Goof Ring	4" LED Slim Panel V3	White	SL4-GR-WH-512-V1 
7 5/8" Goof Ring	6" LED Slim Panel V3	White	SL6-GR-WH-758-V1 
8 5/8" Goof Ring	6" LED Slim Panel V3	White	SL6-GR-WH-858-V1 



Date:	Project:
Prepared for:	Type:
Comments:	

PAST PROJECTS



Kitchen, Dining Area, and Living Room in Private Residence



Stairwell at Club Atwater



Gym at Club Atwater



Corridor at Club Atwater



Kitchen and Dining Area at Club Atwater

